WO 2004/034861 PCT/EP2003/011026

CLAIMS

1. Device for discharging a cooking liquid from a food product cooking apparatus, characterised in that it comprises valve means for intercepting said cooking liquid and outside conveyance means of said apparatus.

- 2. Discharging device according to claim 1, characterised in that said intercepting valve means are placed between said conveyance means and a bowl of said device containing said cooking liquid.
- 3. Discharging device according to one or more of the previous claims, characterised in that said intercepting valve means can be partialised.
- 4. Discharging device according to one or more of the previous claims, characterised in that said intercepting valve means comprise a body connected to said bowl and defining a seat in which a hollow shutter is rotatably connected, mobile between an open position and a closed position.
- 5. Discharging device according to one or more of the previous claims, characterised in that said conveyance means comprise a substantially rigid tube.
- 6. Discharging device according to one or more of the previous claims, characterised in that said substantially rigid tube is connected to said shutter, a recess of said shutter being aligned to a recess of said tube.
- 7. Discharging device according to one or more of the previous claims, characterised in that in said open position

WO 2004/034861 PCT/EP2003/011026

said tube is substantially vertical or tilted upwards and in said closed position said tube is tilted downwards.

- 8. Discharging device according to one or more of the previous claims, characterised in that it comprises a tubular connection element placed between said bowl and said body of said valve means, said connection element being tilted downwards.
- 9. Procedure for discharging a cooking liquid from a food product cooking apparatus, characterised in that it consists of rotating a substantially rigid tube, connected to valve means for intercepting liquid, from an upward orientation to a downward orientation, simultaneously and progressively taking said intercepting means from a closed position to an open position, so as to allow the discharge of said liquid through said intercepting means and said tube.
- 10. Discharging device and procedure according to one or more of the previous claims, characterised in that said food product cooking apparatus is a fryer and said liquid to be discharged is oil.
- 11. Device and procedure for discharging a cooking liquid from a food product cooking apparatus, all as substantially described, represented in the attached tables of drawings and claimed.